# **TECHNICAL FELTS**

www.textilolius.com





SAE R.1

TEXTIL EST. 1946





#### **HEAD OFFICE**

c/ Orient, 78-84, 2ª Planta 17 08172 Sant Cugat del Vallès Barcelona (Spain)

### INTERNATIONAL DEPARTMENT

Tel.: +34 935 831 705 Fax.: +34 935 831 793

e-mail: international@textilolius.com

Our technical felts have properties that make them suitable for use as part of industrial processes or manufactured products.

Their quality is guaranteed by certificates ISO 9001:2015 and OEKO-TEX Standard 100. Our felts are manufactured according to either DIN 61200 Standard or SAE J314b Standard.

We produce a wide range of densities and thicknesses, with 100% pure wool composition or blends of wool and other fibres.

Thermal insulation, anti-vibration, lubricating elements, filters, seals, gaskets or washers are some of the many applications of our felts.

treatments to provide our felts















EXTRA LIGHT COLOUR-FAST







ANTI-STATIC

Ephemeral spaces

Interior design

Automotive



Liquid absorption

**Appliances** 











## SAE J314b STANDARD

# **DURO 1° BLANCO**

DENSITY 0,340 g/cm<sup>3</sup> COMPOSITION 98% BLEACHED WOOL



THICKNESS 1/8" - 3/4" LENGTH 25 - 34 ydWIDTH 60"







# **DURO GRIS**

DENSITY 0,330 g/cm<sup>3</sup> COMPOSITION 86% WOOL



THICKNESS 1/8'' - 3/4''LENGTH 25 - 34 ydWIDTH 60"









## **F50** DURO 1° **BLANCO**

DENSITY 0,325 g/cm<sup>3</sup> COMPOSITION 100% CARBONIZED WOOL



THICKNESS 1/16" - 3/32" LENGTH 45 - 50 ydWIDTH 60′′









## **SEMICARDAS GRIS**

DENSITY 0,267 g/cm<sup>3</sup> COMPOSITION 80% WOOL



**THICKNESS** 1/8" - 1" LENGTH 38 - 42 ydWIDTH 72"













## **SEMICARDAS BLANCO**

DENSITY 0,260 g/cm<sup>3</sup> COMPOSITION 98% CARBONIZED WOOL



**THICKNESS** 1/8′′ – 1′′ LENGTH

38 - 42 yd

WIDTH

60′′











## C-200 **BLANCO**

DENSITY 0,180 g/cm<sup>3</sup> COMPOSITION 98% CARBONIZED WOOL



**THICKNESS** 1/8" - 1" LENGTH 23 - 47 yd

WIDTH

72"









