

# TECHNICAL FELTS

www.textilolius.com



SAE R.2



**HEAD OFFICE**  
c/ Orient, 78-84, 2ª Planta 17  
08172 Sant Cugat del Vallès  
Barcelona (Spain)

**INTERNATIONAL DEPARTMENT**  
Tel.: +34 935 831 705  
Fax.: +34 935 831 793  
e-mail: international@textilolius.com

Our technical felts have properties that make them suitable for use as part of industrial processes or manufactured products.

Their quality is guaranteed by certificates ISO 9001:2015 and OEKO-TEX Standard 100. Our felts are manufactured according to either DIN 61200 Standard or SAE J314b Standard.

We produce a wide range of densities and thicknesses, with 100% pure wool composition or blends of wool and other fibres.

Thermal insulation, anti-vibration, lubricating elements, filters, seals, gaskets or washers are some of the many applications of our felts.

We also offer special treatments to provide our felts with additional properties:



WATER PROOFING



FIRE RESISTANT



ANTI-MOULD



ANTI-PILLING



ANTI MOTH



STAIN RESISTANT



EXTRA LIGHT COLOUR-FAST



STIFFENER



NON-SLIP



ANTI-STATIC

## USES



Orthopaedics



General industry



Baking industry



Musical instrumentation



Liquid absorption



Appliances



Packaging



Metallurgical ind.



Riding saddles



Glass industry



Window displays



Ephemeral spaces



Interior design



Automotive



Footwear



Construction Acoustics



Furniture

# SAE J314b STANDARD


## F1

**DURO 1°  
BLANCO**

DENSITY  
0,340 g/cm<sup>3</sup>  
COMPOSITION  
98% BLEACHED WOOL



THICKNESS  
1/8" – 3/4"  
LENGTH  
25 – 34 yd  
WIDTH  
60"




## F3

**DURO GRIS**

DENSITY  
0,330 g/cm<sup>3</sup>  
COMPOSITION  
86% WOOL



THICKNESS  
1/8" – 3/4"  
LENGTH  
25 – 34 yd  
WIDTH  
60"




## F50

**DURO 1°  
BLANCO**

DENSITY  
0,325 g/cm<sup>3</sup>  
COMPOSITION  
100% CARBONIZED WOOL



THICKNESS  
1/16" – 3/32"  
LENGTH  
45 – 50 yd  
WIDTH  
60"



## F7

**SEMICARDAS  
GRIS**

DENSITY  
0,267 g/cm<sup>3</sup>  
COMPOSITION  
80% WOOL



THICKNESS  
1/8" – 1"  
LENGTH  
38 – 42 yd  
WIDTH  
72"



## F5

**SEMICARDAS  
BLANCO**

DENSITY  
0,260 g/cm<sup>3</sup>  
COMPOSITION  
98% CARBONIZED WOOL



THICKNESS  
1/8" – 1"  
LENGTH  
38 – 42 yd  
WIDTH  
60"



## F10

**C-200  
BLANCO**

DENSITY  
0,180 g/cm<sup>3</sup>  
COMPOSITION  
98% CARBONIZED WOOL



THICKNESS  
1/8" – 1"  
LENGTH  
23 – 47 yd  
WIDTH  
72"



Possible slight colour differences between production lots or colour cards | We can customize compositions, densities and thicknesses | We have the option to dye these products